

THIRD RUBBER RANGE - 12 VOLT

161		BAR	315	58	4	332	133	180	203	1	T1	B12
162		BAR	315	58	4	332	133	180	203	0	T4	B12
165		BAR	265	45	3	235	135	185	210	1	T1	B12
166		BAR	265	45	3	235	135	185	210	0	T4	B12
221		BAR	360	76	5	435	175	180	205	0	T1	N
241		BAR	295	68	5	307	170	200	225	0	T1	N
242		BAR	295	68	5	307	170	200	225	1	T1	N
243		BAR	630	90	6	346	175	210	235	0	T1	N
244		BAR	630	90	6	346	175	210	235	1	T1	N
279	57211	BAR	295	63	4	488	112	200	225	8	T1	N
291		BAR	265	63	4	248	170	200	225	1	T1	N
292		BAR	265	63	4	248	170	200	225	0	T1	N
321		BAR	700	150	8	513	220	200	224	3	T1	N
323		BAR	700	150	8	513	220	200	224	4	T1	N
324		BAR	1050	200	10	513	278	200	224	4	T1	N
325		BAR	1050	200	10	513	278	200	224	3	T1	N
327		BAR	680	120	6	510	194	200	224	3	T1	N
333	63528	BAR	710	135	7	360	253	210	235	6	T1	N
355		BAR	680	125	7	346	175	255	280	0	T1	N
356		BAR	680	125	7	346	175	255	280	1	T1	N
361		BAR	570	90	6	320	175	255	280	1	T1	N
602		BAR	565	85	6	377	172	200	225	1	T1	N
612		BAR	630	95	6	445	175	217	242	1	T1	N
F158	66511	BAR	510	165	8	344	335	212	237	6	T1	N